

Specifications

Model		B1410	B1610	
Engine	Make	Kubota		
	Type	E-TVCS, indirect injection, vertical, liquid cooled, 4 cycle diesel		
	DIN power	kW (PS)	9.6 (13.0)	10.7 (14.5)
	SAE power	kW (HP)	10.3 (14.0)	11.7 (16.0)
	PTO power	kW (PS)	8.1 (11.0)	9.2 (12.5)
	No. of cylinders		3	3
	Total displacement	cm ³	656	719
	Muffler		Fully enclosed	
	Air cleaner		Fully enclosed, dry paper element	
	Fuel tank	ℓ (imp. gal)	13 (2.86)	
Drive train	Driving method	4WD		
	Transmission speed	F6R2		
	max. travelling speed	km/h (mph)	with standard farm tyre	
			15.2 (9.4)	16.2 (10.1)
PTO	Brake type	Wet disc		
	PTO type	Transmission driven with one way clutch		
	Rear PTO speed	rpm	540 /1000	
	Mid PTO speed	rpm	2545	
Hydraulic system				
Pump capacity	ℓ/min (imp. gpm)	14.1 (3.1)		
Lift capacity (lower link)	kg (N, lbs.)	540 (5292, 1190)		
Hydraulic circuit changeover unit		Standard		
Dimensions	Overall length (w/o 3P)	mm (in.)	2035 (80.1)	
	Overall width (min tread)	mm (in.)	with standard farm tyre	
			932 (36.7)	927 (36.5)
	Overall height (steering)	mm (in.)	1235 (48.6)	1255 (49.4)
	Wheelbase	mm (in.)	1270 (50)	
	Ground clearance	mm (in.)	250 (9.8)	270 (10.6)
	Tread (front)	mm (in.)	with standard farm tyre	
			778 (30.6)	767 (30.2)
	Tread (rear)	mm (in.)	711-1031 (28.0-40.6)	
	Weight*	kg (lbs.)	510 (1124)	522 (1151)
	Tyre Farm	front	4.5-10	
		rear	7-16	
	Turf	front	20×8.00-10	
rear		212 / 80D-15		
Turning radius (with 4WD brake)	m (in.)	1.8 (70.9)		
Other	Steering	Manual		
	Water temp. gauge	Standard		
	Fuel gauge	Standard		
	Tachometer	Standard		
	Operator deck	Semi flat		
	Mower cutting width	mm (in.)	1219 (48) ^{**}	

The company reserves the right to change the above specifications without notice.

*Manufacture's estimate.

**Specifications may vary among markets.

**Mower deck can not attach tractor with farm tyre 5-12, 8-16.

©2006 Kubota Corporation



KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
 Phone Thame (01844) 214500 Fax (01844) 216685
 Web site: <http://www.kubota.co.uk/>
 E-mail: sales@kubota.co.uk